

Manual Uninstall of DB2 Web Query V2

To completely remove IBM DB2 Web Query for i, version 2, do the following:

1. Release the user-registered licenses. Enter the command **WRKLICINF 5733WQX** and select option 8 on features 5104, 5105 and 5106. For each licensed user in the lists, enter the following command, where *username* is the user profile and *x* is the last digit of the feature number:
CALL QWEBQRY/QWQRLSLIC ('username' 'x')
2. Enter the command **QWEBQRY/ENDWEBQRY** and wait a few moments for the server jobs to end.
3. Enter the command **GO LICPGM**, select Option 12, and then select Option 4 for all 5733WQX options.
4. Enter the command **EDTF STMF('/qibm/userdata')** and select Option 9 on the qwebqry folder.
5. Enter the command **STRSQL** and run the following statements:
 - a. **DROP SCHEMA QWQREPOS**
 - b. **DROP SCHEMA QWQCENT**
 - c. **DROP SCHEMA QWQRETAIL** (For release 2.2.1 and later.)
6. Press F3 to exit ISQL.
7. Enter the command **WRKAUTL AUTL(QWQ*)** and select Option 4 to delete the authorization lists.
8. Delete the user profiles by entering these commands. It may be necessary to first delete all objects owned by the profile or to remove any group membership from the profile.
 - a. **DLTUSRPRF QWQADMIN**
 - b. **DLTUSRPRF QWQADMGRP** (For release 2.2.1 and later.)